










Model No.	Pictures	Description		
<b>Switch</b>				
EW55912FP		Wireless Management Switch with 8 GE PoE + 2 GE + 2 GE SFP, IEEE802.3at/af, 130w PoE power budget, internal power supply, 13inch 1U rack-mountable.; Switching Capacity:24Gbps		64,710,000
EW57928P		24-Port Managed Gigabit 185W PoE+ Switch With Centralized Network Management(24) 10/100/1000 Mbps Gigabit Ethernet PoE+ Ports; (4) SFP Ports19" Rackmount Supports 802.3af/at PoE & Total Budget of 185W4 Types of In-Switch Network Management OptionsNetwork Troubleshooting, Monitoring & Email Alerts		123,540,000
<b>Indoor Access Points</b>				
EWS360AP		11ac/b/g/n Dual Band Concurrent Indoor Managed AP, 3Tx+3Rx: 450+1300Mbps, 1 x 10/100/1000Mbps LAN Port, High Power 28dBm @ 2.4GHz, 27dBm @ 5GHz, 6 x Integrate Antennas, 802.3af support		CALL
ENHERO 5		The state-of-the-art 802.11ac and MU-MIMO technology brings revolutionary connecting speed and bandwidth for diversity of multimedia applications. EnHero5 equips with two powerful RF interfaces that support up to 867 Mbps in 5GHz frequency band and 400 Mbps in 2.4GHz frequency band (with 4ss/VHT40 clients).		29,420,000
EWS330AP		Indoor Wireless Access PointWi-Fi 5 Wave 2 Managed Compact 11ac Wave 2 Wireless Speeds to 867 Mbps (5 GHz); to 400 Mbps (2.4 GHz)Mesh Wireless Support Simplifies Setup, Optimizes Signals & Self-HealsAdjustable 26 dBm Radios with 5 dBi Integrated Antennas for Improved CoverageUp to 30% Faster Throughput Over 11ac Wave 1 3x3 APsMU-MIMO Improves Performance & Increases User Device Capacities802.3af PoE Port offers easy placement where power outlets are unavailable		34,120,000
EAP1300		Quad-Core Processor, 717 MHz "Turbo Engine", 11ac Wave 2 Speeds to 867 Mbps (5 GHz); to 400 Mbps (2.4 GHz), Up to 30% Faster Throughput Over 11ac Wave 1 2x2 Aps, GIG 802.3af PoE-Compliant for Easy Placement Where Power is Limited, Beamforming Optimizes Antenna Signal, Reception & Reliability for Clients-TX Power=23 dbm		CALL
<b>Outdoor Access Points</b>				
ENS620EXT		2.4GHz+5GHz 11ac/b/g/n Dual Band Concurrent AP (AP/CB/WDS), 2Tx+2Rx: 400+866Mbps, 2 x 10/100/1000Mbps LAN Port, High Power 26dBm @ 2.4GHz, 26dBm @ 5GHz, External 4*SMA connector, 24V PoE, MU-MIMO, Beamforming		48,240,000
ENS610EXT		ENS610EXT equips with two powerful RF interfaces that support up to 867 Mbps in 5GHz frequency band and 400 Mbps in 2.4GHz frequency band (with 2ss/VHT40 clients). With robust IP55 certified casing, this access point is designed to withstand harsh environment conditions including serve and prolonged exposure to sunlight, extreme cold, frost, snow, rainfall, hail and humidity.		35,300,000

ENGENIUS

1400-06-08

