




















































































































HiLook-DVR				
	Items	Description	User Price	
1	THC-B110-M	1 MP high-performance CMOS, 1280 × 720 resolution, 2.8 mm, 3.6 mm, 6 mm fixed lens, Day/Night switch, EXIR 2.0, smart IR, up to 20 m IR distance, 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), IP66	IRR 4,810,000	
2	THC-B120-P	2 MP high-performance CMOS-1920 × 1080 resolution-2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66	IRR 6,500,000	
3	THC-B120-MS	2 MP Audio Fixed Mini Bullet Camera Smart IR, up to 20 m IR distance Water and dust resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) With built-in microphone, enhancing your safety with video and audio together	IRR 7,350,000	
4	THC-B120-M	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66-METAL	IRR 7,090,000	
5	THC-B120-MPIRL	2 MP PIR Fixed Mini Bullet Camera 2 MP, 1920 × 1080 resolution, 2.8 mm, 3.6 mm fixed focal lens, Smart IR, up to 20 m IR distance, PIR detection, strobe light alarm IP66	IRR 7,630,000	
6	THC-B140-P	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) --DWDR-BLC-IP66	IRR 7,240,000	
7	THC-B140-M	4MP high-performance CMOS -2560 × 1440 resolution- 2.8 mm- fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-IP 66-BLC-Full Metal	IRR 7,990,000	
8	THC-B220	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-Switchable TVI/AHD/CVI/CVBS-IP66	IRR 7,590,000	
9	THC-B220C	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-Switchable TVI/AHD/CVI/CVBS-IP66	IRR 7,100,000	
10	THC-B220-M	2MP CMOS Sensor, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR- OSD Menu, IP66, 2.8/3.6/6mm Lens, Support HD- TVI/AHD/CVI/CVBS video output-Full Metal	IRR 8,440,000	
11	THC-B240	4MP high-performance CMOS -2560 × 1440 resolution- 2.8 mm- fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-BLC-IP 66	IRR 9,110,000	
12	THC-B240-M	4MP CMOS Sensor, EXIR Bullet, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR, OSD Menu, IP66, 2.8/3.6/6mm Lens, Support HD- TVI/AHD/CVI/CVBS video output-Full Metal	IRR 9,940,000	
13	THC-T110-P	1 MP high-performance CMOS, 1280 × 720 resolution, 2.8 mm, 3.6 mm, 6 mm fixed focal lens, Day/Night switch, EXIR 2.0, smart IR, up to 20 m IR distance, 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), Switchable TVI/AHD/CVI/CVBS. Pelastic case	IRR 3,460,000	
14	THC-T120-PC	2 MP high-performance CMOS- 1920 × 1080 resolution-2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 4,900,000	
15	THC-T120	2 MP high-performance CMOS- 1920 × 1080 resolution-2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 7,400,000	
16	THC-T123	2 MP EXIR Turret Camera-performance CMOS- Ultra low light- 1920 × 1080 resolution- 2.8 mm, 3.6 mm, 6 mm fixed lens- Day/Night switch EXIR 2.0, smart IR, up to 30 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)	IRR 6,000,000	
17	THC-T120-MS	2 MP Audio Fixed Turret Camera Smart IR, up to 20 m IR distance Water resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) With built-in microphone, enhancing your safety with video and audio together	IRR 7,350,000	
18	THC-T120-M	2 MP high-performance CMOS- 1920 × 1080 resolution-2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	IRR 6,270,000	
19	THC-T140-P	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm, Fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66	IRR 7,340,000	
20	THC-T140	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm, Fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66	IRR 7,400,000	
21	THC-T140-M	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm, Fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66-METAL	IRR 8,400,000	
22	THC-T220-P	2 MP high-performance CMOS-1920 × 1080 resolution-2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 6,580,000	
23	THC-T220-PC	2 MP Fixed Turret Camera Smart IR, up to 40 m IR distance Water resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 6,380,000	

24	THC-T220-MC	HiLook 2MP EXIR Turret Cam with Fixed Lens 1080p turret camera Smart IR, up to 40 m IR distance Water resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 7,400,000	
25	THC-T220-MS	2 MP Audio Fixed Turret Camera Smart IR, up to 40 m IR distance Water resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) With built-in microphone, enhancing your safety with video and audio together	IRR 8,760,000	
26	THC-T220-M	2 MP high-performance CMOS-1920 x 1080 resolution-2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	IRR 7,710,000	
27	THC-T240-P	4 MP high-performance CMOS-2560 x 1440 resolution-2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66	IRR 8,740,000	
28	THC-T240-M	4 MP high-performance CMOS-2560 x 1440 resolution-2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66-METAL	IRR 9,900,000	
Vari-Focal Series				
29	THC-B320-VF	2MP CMOS Sensor, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DWDR, DNR, OSD Menu, IP66, 2.8-12mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	IRR 15,200,000	
30	THC-B340-VF	4MP CMOS Sensor - 2.8-12mm Vari Focal Lens, EXIR Bullet, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR, OSD Menu, IP66, Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	IRR 16,780,000	
31	THC-D320-VF	2MP CMOS Sensor, 40m IR, EXIR Dome, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu, IP66, 2.8-12mm Vari Focal Lens--support HD-TVI/AHD/CVI/CVBS video output.-IK10-Full Metal	IRR 14,900,000	
32	THC-D340-VF	4MP CMOS Sensor, EXIR Dome, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens, IK10. Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 16,110,000	
33	THC-T320 VF	2MP CMOS Sensor, 40m IR, EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu, IP66, 2.8-12mm Vari Focal Lens. Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic- Eyeball: Metal	IRR 13,780,000	
34	THC-T340-VF	4MP CMOS Sensor, EXIR Eyeball, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens. Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic-Eyeball: Metal	IRR 15,070,000	
Turbo HD PTZ Camera				
35	PTZ-T4225I-D	1/2.8" HD progressive scan CMOS 1920 x 1080 resolution 25x optical zoom, 16x digital zoom 20 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	IRR 71,040,000	
36	PTZ-T4215I-D	1/2.8" HD progressive scan CMOS 1920 x 1080 resolution 15x optical zoom, 16x digital zoom 20 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	call	
37	PTZ-T5225I-A	1/2.8" HD progressive scan CMOS 1920 x 1080 resolution 25x optical zoom DWDR (Digital Wide Dynamic Range) Up to 150 m IR distance 3D intelligent positioning Switchable turbo HD and CVBS outputs	call	
DVR 4 Channel				
38	DVR-104G-F1	4-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP). Long distance transmission over UTP and coaxial cable. H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs. Supports 1080p Lite. Encoding ability up to 1080p Lite @ 12 fps, One HDD for continuous video recording, Smart search for efficient playback.	IRR 8,830,000	
39	DVR-204G-F1	Recording Capability HD1080p Lite 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, 1-ch Up to 960P resolution, 1 SATA (6TB) interface, HD1080p Lite @ 25 fps/ch, 260 1U case-HDMI output HD1080p-Metal	IRR 11,120,000	
40	DVR-204Q-F1	Recording Capability 3MP 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, 1-ch IP video input (up to HD1080p resolution), 1 SATA (6TB) interface, CH 1: 3MP @ 12 fps, CH 2-4: 1920x1080P: 12 fps/ch, 260 1U case-HDMI output HD1080p-Metal	IRR 12,370,000	
41	DVR-204Q-K1	H265+ compression saving up to 50% on bandwidth and storage. Recording 2MP @ 15FPS on 1080P or @ 25FPS on 1080PLite (3MP @ 15FPS on channel 1) Support self-adaptive HDTV/HDCVI/AHD/CVBS signal input. Add up to 2 x 6MP IP cameras. HDMI output at 1920 x 1080 resolution Up to 4-ch synchronous playback at 1080p resolution playback at up to 256X speed.	IRR 15,490,000	
42	DVR-204U-F1	Recording Capability 5MP/3MP 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, 2-ch IP video input (up to 6MP resolution), 1 SATA (6 TB)-interface, 5MP @ 12fps, 4MP @ 15fps, 3MP @ 18fps, 1080p/720p/WD1/4CIF/VGA/CI@ 25fps (P)/30fps (N), 315 1U case-HDMI output HD1080p-Metal	IRR 19,020,000	
43	DVR-204U-K1	Self-adaptive HDTV/HDCVI/AHD/CVBS signal input 1 Up to 8/16-ch 8 MP IP cameras input for DVR-204/208U-K1 1 8 MP/5 MP/4 MP HDTV video input and live view for DVR-208U-K1, and 5MP/4 MP for DVR-204U-K1 1 Defogging function enabled for the supported analog cameras 1 Long distance transmission over UTP and coaxial cable; max. 800m for 1080p and 1200m for 720p HDTV signal	IRR 22,170,000	
DVR 8 Channel				

44	DVR-108G-F1	8-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP). Long distance transmission over UTP and coaxial cable. H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs. Supports 1080p lite. Encoding ability up to 1080p lite @ 12 fps. One HDD for continuous video recording. Smart search for efficient playback.	IRR 15,050,000	
45	DVR-208G-F1	Recording Capability HD1080p Lite 8-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch Up to 960P resolution), 1 SATA(6TB) interface, HD1080p Lite @ 12 fps/ch, 260 1U case-HDMI output HD1080p-Metal	IRR 18,380,000	
46	DVR-208Q-F1	Recording Capability 3MP 8-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input (up to HD1080p resolution), 1 SATA(6TB) interface, CH 1 & 2: 3MP @ 12 fps, CH 3 - 8:1920x1080P: 12 fps/ch, 260 1U case-HDMI output HD1080p-Metal	IRR 30,700,000	
47	DVR-208Q-K1	Connectable to turbo HD, AHD, HDCVI and analog cameras. 2-ch 1080p IP cameras input. Long distance transmission over UTP and coaxial cable. One key enable H.264+ compression. Up to 3 MP resolution for recording of the first 2 channels. Supports real-time 1080p lite. Simultaneous HDMI/VGA output at up to 1920 x 1080 resolution. One SATA interface (up to 6TB capacity per HDD).	IRR 27,070,000	
48	DVR-208Q-K2	8-ch 1080p 1U H.265 DVR-5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP)- Long distance transmission over UTP and coaxial cable. H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs. Supports 4 MP lite, and when enabled the image effect is similar with 4 MP. Encoding ability up to 1080p lite @ 15 fps. Two HDDs for continuous video recording. Smart search for efficient playback.	IRR 32,000,000	
49	DVR-208U-F1	Recording Capability 5MP/3MP 8-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, 4-ch IP video input (up to 6MP resolution), 1 SATA(6 TB) interface, 5MP@12fps, 4MP@15fps, 3MP@18fps, 1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case-HDMI output 4K-Metal	IRR 38,140,000	
50	DVR-208U-K1	8 Channel DVR, Support HD-TVI, AHD, HD-CVI and analog cameras. Supports 4 x IP Camera, 1080P resolution real-time recording. 8MP recording @ 8fps, VGA output at up to 1920 x 1080P resolution. HDMI output at up to 4K (3840 x 2160) resolution. Supports H.265+ Support up to 8-ch synchronous playback, Internet & Smart Phone compatible	IRR 41,080,000	
Digital Video Recorder				
51	DVR-116G-F1	16-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP). Long distance transmission over UTP and coaxial cable. H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs. Supports 1080p lite. Encoding ability up to 1080p lite @ 12 fps. One HDD for continuous video recording. Smart search for efficient playback.	IRR 21,000,000	
52	DVR-216G-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input (up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4K-Metal	IRR 26,570,000	
53	DVR-216G-K1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input (up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4K-Metal	IRR 26,570,000	
54	DVR-216Q-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input (up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4K-Metal	IRR 37,620,000	
55	DVR-216Q-F2	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input (up to HD1080p resolution), 2 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4K-Metal	call	
56	DVR-216Q-K1	One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite	IRR 46,440,000	
57	DVR-216Q-K2	One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite	IRR 48,820,000	
58	DVR-216U-F2	Recording Capability 5MP/3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -8-ch IP video input (up to 6MP resolution), 2 SATA (6 TB)- interface, 5MP@12fps, 4MP@15fps, 3MP@18fps, 1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 380 1U case-HDMI output 1ch 4K-Metal	IRR 72,210,000	
59	DVR-216U-K2	DVR 16 Channels HD 8 Megapixel, Interfaces input: 16 video / 1 Audio, (Support TVI - AHD - CVI - CVBS, HDMI, VGA Outputs, 2 USB Support H.265+ compression, 2SATA up to 8TB capacity per HDD, Up to 8-ch, 6MP IP cameras input, Up to 8 MP resolution for recording	IRR 81,300,000	
60	DVR-232G-K2	32-ch 1080p Lite 1U H.265 DVR, transmission over UTP and coaxial cable. H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs. Supports 1080p lite, and when enabled the image effect is similar with 1080p. Encoding ability up to 1080p lite @ 12 fps, 2HDDs for continuous video recording	IRR 72,920,000	
61	DVR-232Q-K2	32-ch 1080p 1U H.265 DVR 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs. Supports 4 MP lite, and when enabled the image effect is similar with 4 MP. Encoding ability up to 1080p lite @ 15 fps 2 HDDs for continuous video recording	IRR 91,580,000	

Hilook-NVR			
Items	Description	User Price	
1	IPC-B120 1/2.8" progressive scan CMOS-1920 x 1080@30fps -2.8mm fixed lens- H.264+, H.264- Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR	IRR 14,280,000	
2	IPC-B120-D/W 2 MP Outdoor Fixed Bullet Network Camera with Build-in Mic High quality imaging with 2 MP resolution Efficient H.264 compression technology to save bandwidth and storage Clear imaging against strong back light due to DWDR technology Built-in microphone for real-time audio security Wireless connection for convenient installation and use	IRR 13,570,000	
3	IPC-B120H 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080-25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, -2.8/4/6mm fixed lens-BLC, DC12V & PoE, up to 30m IR-Support mobile monitoring via Hik-Connect *power supply no included-DWDR-Front Cover: Metal-Back Cover & Bracket: Plastic-IP67	IRR 15,050,000	
4	IPC-B121H 1/2.8" progressive scan CMOS (3D DNR) 1920 x 1080@30fps (Up to 30 m IR range) 2.8mm/4 mm fixed lens (IP67, DWDR, H265	IRR 15,050,000	
5	IPC-B121H-M 2 MP Fixed Bullet Network Camera High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology, (IP67) EXIR 2.0: advanced infrared technology with long IR range	IRR 15,850,000	
6	IPC-B140H 4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE, 2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Connet *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	IRR 18,610,000	
7	IPC-B140H-M 4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE, 2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Connet *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	IRR 20,360,000	
8	IPC-B150H-M High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology	IRR 22,620,000	
9	IPC-B220 Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application	IRR 16,240,000	
10	IPC-B220-D Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application- D model only support 12VDC power supply	IRR 15,520,000	
11	IPC-T120 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080-25fps(P)/30fps(N), DWDR -H.264+&H.264-2.8/4/6mm fixed lens- BLC, - DC12V & PoE -up to 10m IR- Support mobile monitoring via Hik-Connect *power supply no included-Eyeball-Plastic-Cover: Plastic-Indoor-ip67	IRR 14,900,000	
12	IPC-T120-D 1/2.8" progressive scan CMOS-Up to 2.0 megapixel 2.8 mm fixed focal lens-H264+ - 10 m IR range-Dual stream-DWDR-3D DNR (Digital Noise Reduction)- Mobile monitoring via mobile application-IP 67- D model only support 12VDC power supply	IRR 14,170,000	
13	IPC-T220-H 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080-25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR-DWDR, BLC, DC12V & PoE -up to 30m IR-Support mobile monitoring via HikConnect *power supply no included2.8/4/6mm fixed lens-Eyeball: MetalCover: Plastic-IP67	IRR 17,190,000	
14	IPC-T221-H 2 MP Fixed Turret Network Camera High quality imaging with 2 MP resolution, Efficient H.265+ Clear imaging against strong back light by DWDR technology Water and dust resistant (IP67) (PoE) technology	IRR 17,210,000	
15	IPC-T220 1/2.8" progressive scan CMOS BLC/3D DNR, 1920 x 1080@30fps, IP67 2.8, 4, 6 mm fixed lens, Digital WDR, H.264+, H.264- Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)	IRR 16,980,000	
16	IPC-T240H 4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/N), H.265+/H265/H.264+&H.264, up to 30m IR- 3D DNR-DWDR, BLC, DC12V & PoE-2.8/4/6mm fixed lens- Support mobile monitoring via Hik-Connect *power supply no included-Eyeball: Metal-Cover: Plastic- IP67	IRR 21,360,000	
17	IPC-D120 1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps-2.8mm fixed lens-H.264+, H.264- Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR- IK 10	IRR 15,600,000	
18	IPC-D120H 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080-25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, -2.8/4/6mm fixed lens- BLC, DC12V & PoE, DWDR- Support mobile monitoring via Hik-Connect *power supply no included-up to 30m IR-Base: Metal-Cover: Plastic-IP67, IK10	IRR 16,040,000	
19	IPC-D121H 2 MP Fixed Dome Network Camera Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology Water and dust resistant (IP67) and vandal proof (IK10) Easy installation with power over Ethernet (PoE) technology	IRR 15,930,000	
20	IPC-D121H-M 2 MP Fixed Dome Network Camera Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology Water and dust resistant (IP67) and vandal proof (IK10) Easy installation with power over Ethernet (PoE) technology-METAL CASE	IRR 17,540,000	
21	IPC-D140H 4.0 MP IR NetworkDome Camera, 1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps (Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens, PoE Power over Ethernet), H.265+, H.265, H.264+, H.264 (IP67, IK10, Dual stream, 120 dB WDR.	IRR 19,780,000	
22	IPC-D150H High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) and vandal resistant (IK10) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology	IRR 19,940,000	
Vari-Focal Series			
23	IPC-B620H-V 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080-25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR -DWDR- BLC, DC12V & PoE, TF card slot, up to 30m IR-Support mobile monitoring via Hik-Connect *power supply no included-2.8"-12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 33,050,000	

24	IPC-B620H-Z	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.264+&H.264, 3D DNR, BLC, up to 30m IR-DC12V & PoE, -DWR- TF card slot, Support mobile monitoring via Hik-Connect *power supply no included-2.8"-12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 37,550,000	
25	IPC-B621-V	2 MP Varifocal Bullet Network Camera Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to DWDR technology(IP66) -V: model with manual vari-focal lens Built-in microphone enhances safety with video/audio in tandem	IRR 31,980,000	
26	IPC-B621-Z	2 MP Varifocal Bullet Network Camera High quality imaging with 2 MP resolution, Efficient H.265+ Clear imaging against strong back light due to DWDR technology(IP66) -Z: model with motorized vari-focal lens Built-in microphone enhances safety with video/audio in tandem	IRR 36,410,000	
27	IPC-B640H-V	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, up to 30m IR-DC12V & PoE, TF card slot, WDR-Support mobile monitoring via Hik-Connect *power supply no included-2.8"-12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 36,560,000	
28	IPC-B640H-Z	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, up to 30m IR-DC12V & PoE, TF card slot, -WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8"-12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 39,160,000	
29	IPC-T620-Z	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.264+&H.264, 3D DNR, BLC, -WDR- up to 30m IR-DC12V & PoE, Support mobile monitoring via Hik-Connect *power supply no included-2.8"-12mm VF lens-Eyeball: MetalCover: Plastic-IP67	IRR 33,620,000	
30	IPC-D620H-V	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, -DWR- 3D DNR, BLC, 2.8"-12mm vari-focal lens - DC12V & PoE, TF card slot, up to 30m IR- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	IRR 32,090,000	
31	IPC-D620H-Z	1/2.8" progressive scan CMOS-2 MP-1920 × 1080@30fps- 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens- H.265+, H.265, H.264+, H.264-Dual stream- DWDR -3D DNR (Digital Noise Reduction)-Up to 30 m IR range-PoE (Power over Ethernet)- IP67, IK10	IRR 35,900,000	
32	IPC-D640H-V	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)(N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot: --2.8"-12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	IRR 35,380,000	
33	IPC-D640H-Z	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)(N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot: --2.8"-12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	IRR 38,060,000	
PanoVu Mini Series IR Network PTZ Camera				
34	PTZ-P332ZI-DE3	System Functions 1 3-ch panoramic images in different directions and 1-ch close-up image 1 PTZ linkage! Up to 10 m IR radius Panoramic Camera! Three 1/2.8" progressive scan CMOS 3-ch 1920 × 1080@30fps resolution! Horizontal FOV: 128.5° × 3 PTZ Camera! 1/2.8" progressive scan CMOS! Up to 1920 × 1080@30fps resolution! 4x optical zoom, 8x digital zoom	IRR 159,000,000	
IP PTZ Camera				
35	PTZ-N4215-DE3	1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution/Min. illumination Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC, 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI	IRR 72,810,000	
36	PTZ-N4215I-DE	1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance! 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI	IRR 77,880,000	
37	PTZ-N4225I-DE	1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR up to 100 m IR distance 25x optical zoom, 16x digital zoom! 120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI	IRR 94,590,000	
38	PTZ-N2404I-DE3	Two-inch 4 MP camera with pan, tilt and zoom (4x) ability Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Great night-time performance with up to 20 m enhanced IR Water and dust resistant (IP66), and vandal proof (IK10)	IRR 50,020,000	
Network Video Recorder				
39	NVR-104-B	Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input -Max (up to 4-ch IP video), Output Bandwidth 40Mbps- H.264, 1 SATA Interface 6TB, mini iU case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability- 2-ch@4MP-4-ch@1080p	IRR 9,810,000	
40	NVR-108-B	Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input -Max (up to 8-ch IP video), Output Bandwidth 40Mbps- H.264, 1 SATA Interface 6TB, mini iU case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability- 2-ch@4 MP, 4-ch@1080p	IRR 12,030,000	
41	NVR-108-B/8p	4-ch Mini iU 4 PoE 4K NVR, Up to 8 channel IP cameras can be connected Plug & Play with 8 Power-over-Ethernet (PoE) Interfaces Supports decoding H.264/H.264 multiple video formats Up to 4-ch @ 1080p decoding capability 1 HDD for continuous video recording	IRR 30,490,000	
42	NVR-104H-D	4-ch Mini iU 4 PoE NVR H.265+/H.265/H.264+&H.264 video compression Up to 40 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth Up to 4-ch network camera inputs, Up to 4-ch 1080p decoding capability HDMI and VGA simultaneous output	IRR 10,400,000	
43	NVR-108H-D	4-ch Mini iU NVR H.265+/H.265/H.264+&H.264 video compression Up to 60 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth Up to 8-ch network camera inputs, Up to 4-ch 1080p decoding capability HDMI and VGA simultaneous output	IRR 13,610,000	

44	NVR-104MH-C	Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8MP),Output Bandwidth 80Mbps- H.265-, 1 SATA (6TB)Interface, standalone 1U 315 case(Metal)-HDMI Output 1Ch 4K, --Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 15,590,000	
45	NVR-104MH-D	Up to 4 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording.	IRR 12,510,000	
46	NVR-104MH-D/4P	Up to 4 channel IP cameras can be connected Plug & Play with 4 Power-over-Ethernet (PoE) Interfaces Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording	IRR 21,660,000	
47	NVR-104MH-C/4P	Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8 MP),Output Bandwidth 80Mbps- H.265-, 1SATA (6TB) Interface, 4 independent PoE network interfaces, 1U 315 case(Metal)-HDMI Output 1ch 4k-Decoding Capability: 1-ch @ 8 MP 4-ch @ 1080P	IRR 22,860,000	
48	NVR-108MH-C	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP),Output Bandwidth 80Mbps- H.265-, 1 SATA Interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1Ch 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 20,970,000	
49	NVR-108MH-D	IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	IRR 16,800,000	
50	NVR-208MH-C	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP),Output Bandwidth 80Mbps- H.265-, 2 SATA Interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1Ch 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 22,820,000	
51	NVR-108MH-C/8P	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8mp),Output Bandwidth 80Mbps- H.265-, 1 SATA Interface(6 TB),8 independent PoE network interfaces, standalone 1U 315 case(Metal)-HDMI Output 1ch 4k, - Decoding Capability:1-ch @ 8 MP / 4-ch @ 1080p	IRR 53,500,000	
52	NVR-108MH-D/8P	IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	IRR 47,520,000	
53	NVR-116MH-C	Recording at up to 8 MP resolution-160Mbps Bit Rate Input- Max (up to 16-ch IP video UP to 8MP),Output Bandwidth 80Mbps- H.265-, 1 SATA Interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1Ch 4K, Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 24,530,000	
54	NVR-216MH-C	Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video),Output Bandwidth 80Mbps, - H.265-2,SATA up to 6TB per HDD interface, standalone 1U 385 case(Metal)-HDMI Output 1 ch 4k -Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 29,190,000	
55	NVR-216MH-C/16P	Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video)Output Bandwidth 80Mbps, H.265-, 2 SATA (up to 6TB per HDD) interface,16 independent PoE network interfaces, standalone 1U 385 case(Metal)-HDMI Output 1 ch 4k, Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 62,680,000	